Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu VF 710 / 55 R 30 NRO, Torquemax 165 D, TL, Steel Belted
CEAT

Product-No.: 10003414

Technical Information:

Product number	10003414
Tyre Size	VF 710 / 55 R 30 NRO
R / D	Radial
TL / TT	TL
LI / SI	165 D
Profil	Torquemax
Manufacturer	CEAT
Specification	R1-W, Steel Belted
Recom. Rim	DW25B
Permissible rim	DW23B
Width mm	715
Outer diameter mm	1544
Static radius mm	671
Rolling circumference mm	4560
Payload in kg at kph (1)	5150 / 65
Payload in kg at kph (2)	5150 / 40
Inflation pressure bar	1,60
Weight kg	205,3
Tyre content 75% litre	443.00
Number of studs	18x2
Certified	ECE 106
NRO	NRO
Nominal width [mm]	710
Aspect ratio	55
Tyre technology	VF
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopa Ceat Torquemax este o anvelopă pentru tractoare de înaltă performantă.
- Designul său asigură o compactare mai redusă a solului, o tractiune ridicată si o bună manevrabilitate atât pe câmp, cât si la transportul pe sosea.
- Crampoanele anvelopei sunt usor înclinate în centrul benzii de rulare pentru a asigura caracteristici bune de rulare pe sosea.
- Unghiul mai plat al crampoanelor de pe umărul anvelopei asigură o tractiune excelentă în timpul lucrărilor pe câmp.
- Umerii rotunjiti ai anvelopei protejează solul si plantele.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.