Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 460 / 70 R 24, 608 165 A2 / 154 B, TL, Steel Belted (17.5L24), Alliance

Product-No.: 10003670

Technical Information:

Product number	10003670
Tyre Size	460 / 70 R 24
R / D	Radial
TL / TT	TL
LI / SI	165 A2 / 154 B
Profil	608
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	W15
Width mm	455
Outer diameter mm	1254
Static radius mm	557
Rolling circumference mm	3635
Payload in kg at kph (1)	5150 / 10
Payload in kg at kph (2)	3750 / 50
Inflation pressure bar	4,00
Weight kg	102,7
Stud height mm	27,8
Number of studs	23x2
Certified	ECE 106
Nominal width [mm]	460
Aspect ratio	70
Tread symmetry	simetrice

Hints and features:

- Anvelopă radială MPT pentru utilaje compacte / de constructii, cum ar fi excavatoare, încărcătoare frontale pe roti, încărcătoare telescopice si încărcătoare antiderapante cu direcţie.
- Bandă de contact solidă pentru stabilitate, în combinatie cu crampoane centrale late pentru suprafete dure.
- Crampoane înalte în zona umerilor pentru tractiune pe suprafete moi.
- Rezistenta optimizată la rulare permite economii de combustibil.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.