Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu 440 / 80 R 28, MULTILOADMAX 163 A8 / 158 D, TL, Steel Belted, M+S CEAT

Product-No.: 10003413

Technical Information:

Product number	10003413
Tyre Size	440 / 80 R 28
R / D	Radial
TL / TT	TL
LI / SI	163 A8 / 158 D
Profil	MULTILOADMAX
Manufacturer	CEAT
Specification	M+S, Steel Belted
Recom. Rim	DW14L
Permissible rim	DW15L
Width mm	441
Outer diameter mm	1415
Static radius mm	641
Rolling circumference mm	4268
Payload in kg at kph (1)	4875 / 40
Payload in kg at kph (2)	4250 / 65
Inflation pressure bar	4,00
Weight kg	111,5
Tyre content 75% litre	246.00
Stud height mm	27,2
Number of studs	42x2
Certified	ECE 106
M+S	M+S
Nominal width [mm]	440
Aspect ratio	80
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopa Ceat Multiloadmax este o anvelopă radială pentru tractoarele gospodăriei comunale, buldoexcavatoare, excavatoare si vehicule agricole.
- Profilul canelurilor în bloc oferă o tractiune foarte bună, o aderentă bună si un comportament de conducere excelent pe teren si pe sosea.
- Blocurile mai mari din centrul benzii de rulare asigură o bună stabilitate în timpul deplasării pe sosea.
- Carcasa cu centură de otel permite o distributie ideală a presiunii la sol si o uzură lentă si uniformă.
- Constructia ranforsată cu talon garantează capacităti portante ridicate si o asamblare usoară.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.