Bohnenkamp
Moving Professionals

CEAT SPECIALTY



# Pneu 600 / 55 R 26.5, Floatmax RT 165 D, TL, Steel Belted CEAT

**Product-No.: 10003815**

**Technical Information:**

| | |
|---|---|
| Product number | 10003815 |
| Tyre Size | 600 / 55 R 26.5 |
| R / D | Radial |
| TL / TT | TL |
| LI / SI | 165 D |
| Profil | Floatmax RT |
| Manufacturer | CEAT |
| Specification | I2, Steel Belted |
| Recom. Rim | AG20.00 |
| Width mm | 611 |
| Outer diameter mm | 1336 |
| Static radius mm | 608 |
| Rolling circumference mm | 4050 |
| Payload in kg at kph (1) | 5150 / 65 |
| Payload in kg at kph (2) | 7004 / 40 |
| Inflation pressure bar | 4,00 |
| Weight kg | 148 |
| Tyre content 75% litre | 358.00 |
| Stud height mm | 24,0 |
| Number of studs | 30x2 |
| Certified | ECE 106 |
| Nominal width [mm] | 600 |
| Aspect ratio | 55 |
| Direction bound | Yes |
| Tread symmetry | simetrice |

**Hints and features:**

- Anvelopa Ceat Floatmax RT este o anvelopă radială pentru remorci agricole, mini-cisterne, masini de împrăstiat îngrăsăminte (masini de fertilizat) si vehicule similare.
- Profilul special permite o auto-curătare foarte bună.
- Compusul de cauciuc rezistent si carcasa din nailon puternic asigură o bună protectie împotriva uzurii premature si o capacitate mare de încărcare la viteze mari.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.