



Pneu 580 / 65 R 22.5, Floatmax RT
166 D, TL, Steel Belted
CEAT

Product-No.: 10003816

Technical Information:

Product number	10003816
Tyre Size	580 / 65 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	166 D
Profil	Floatmax RT
Manufacturer	CEAT
Specification	I2, Steel Belted
Recom. Rim	AG16.00
Width mm	577
Outer diameter mm	1318
Static radius mm	601
Rolling circumference mm	3996
Payload in kg at kph (1)	5300 / 65
Payload in kg at kph (2)	7208 / 40
Inflation pressure bar	4,00
Weight kg	126,5
Tyre content 75% litre	351.00
Stud height mm	20,0
Number of studs	30x2
Certified	ECE 106
Nominal width [mm]	580
Aspect ratio	65
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopa Ceat Floatmax RT este o anvelopă radială pentru remorci agricole, mini-cisterne, masini de împrăștiat îngrășăminte (masini de fertilizat) si vehicule similare.
- Profilul special permite o auto-curățare foarte bună.
- Compusul de cauciuc rezistent si carcasa din nailon puternic asigură o bună protecție împotriva uzurii premature si o capacitate mare de încărcare la viteze mari.