Bohnenkamp
Moving Professionals

CEAT SPECIALTY



# Pneu 250 / 80 R 16, MULTILOADMAX 127 A8 / 123 D, TL, Steel Belted, M+S CEAT

**Product-No.: 10003846**

**Technical Information:**

| | |
|---|---|
| Product number | 10003846 |
| Tyre Size | 250 / 80 R 16 |
| R / D | Radial |
| TL / TT | TL |
| LI / SI | 127 A8 / 123 D |
| Profil | MULTILOADMAX |
| Manufacturer | CEAT |
| Specification | M+S, Steel Belted |
| Recom. Rim | W7 |
| Permissible rim | W8, W9 |
| Width mm | 265 |
| Outer diameter mm | 810 |
| Static radius mm | 367 |
| Rolling circumference mm | 2443 |
| Payload in kg at kph (1) | 1750 / 40 |
| Payload in kg at kph (2) | 1550 / 65 |
| Inflation pressure bar | 4,50 |
| Weight kg | 26,5 |
| Tyre content 75% litre | 47.00 |
| Stud height mm | 17,0 |
| Number of studs | 42x2 |
| Certified | ECE 106 |
| M+S | M+S |
| Nominal width [mm] | 250 |
| Aspect ratio | 80 |
| Direction bound | Yes |
| Tread symmetry | simetrice |

**Hints and features:**

- Anvelopa Ceat Multiloadmax este o anvelopă radială pentru tractoarele gospodăriei comunale, buldoexcavatoare, excavatoare si vehicule agricole.
- Profilul canelurilor în bloc oferă o tractiune foarte bună, o aderentă bună si un comportament de conducere excelent pe teren si pe sosea.
- Blocurile mai mari din centrul benzii de rulare asigură o bună stabilitate în timpul deplasării pe sosea.
- Carcasa cu centură de otel permite o distributie ideală a presiunii la sol si o uzură lentă si uniformă.
- Constructia ranforsată cu talon garantează capacităti portante ridicate si o asamblare usoară.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.