Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 600 / 55 - 26.5, Forestar 644 III 24 PR, 177 A2 / 170 A8, TL, LS-2, Steel Belted Alliance

Product-No.: 10003819

Technical Information:

Product number	10003819
Tyre Size	600 / 55 - 26.5
R / D	Diagonală
TL / TT	TL
LI / SI	177 A2 / 170 A8
PR	24
Profil	Forestar 644 III
Manufacturer	Alliance
Specification	LS-2, Steel Belted
Recom. Rim	AG20.00
Width mm	600
Outer diameter mm	1340
Static radius mm	629
Rolling circumference mm	4102
Payload in kg at kph (1)	7300 / 10
Payload in kg at kph (2)	6000 / 40
Inflation pressure bar	6,00
Weight kg	216,3
Tyre content 75% litre	480.00
Stud height mm	51,0
Number of studs	16x2
Certified	ECE 106
Nominal width [mm]	600
Aspect ratio	55
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.