Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu VF 750 / 60 R 30.5, Floatmax VF X3 187 D, TL, Steel Belted
CEAT

Product-No.: 10004255

Technical Information:

Product number	10004255
Tyre Size	VF 750 / 60 R 30.5
R / D	Radial
TL / TT	TL
LI / SI	187 D
Profil	Floatmax VF X3
Manufacturer	CEAT
Specification	Steel Belted
Recom. Rim	AG24.00
Width mm	780
Outer diameter mm	1678
Static radius mm	722
Rolling circumference mm	5008
Payload in kg at kph (2)	12577 / 40
Inflation pressure bar	3,20
Weight kg	236,5
Tyre content 75% litre	796.00
Stud height mm	26,2
Number of studs	24x2
Certified	ECE 106
Nominal width [mm]	750
Aspect ratio	60
Tyre technology	VF
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopa Ceat Floatmax VF X3 este o anvelopă "flotation" VF de ultimă generatie.
- Este deosebit de potrivită pentru utilizarea pe remorci agricole, cărucioare încărcătoare, masini de împrăstiat îngrăsăminte (masini de fertilizat) si vehicule similare.
- Profilul directional al benzii de rulare, cu crampoane robuste, asigură o tractiune foarte bună, aderentă si auto-curătare.
- Carcasa ei puternică din otel si compusul robust de cauciuc garantează o bună rezistentă la uzură.
- Tehnologia VF permite aceeasi capacitate de încărcare cu o presiune de aer cu 40% mai mică în comparatie cu anvelopele standard de aceeasi dimensiune.
- Acest lucru înseamnă un consum mai mic de combustibil, o compactare mai redusă a solului si productii mai mari.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.