Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 650 / 65 R 38, Forestar 668 III 169 D, TL, R1-W, Steel Belted Alliance

Product-No.: 10004451

Technical Information:

Product number	10004451
Tyre Size	650 / 65 R 38
R / D	Radial
TL / TT	TL
LI / SI	169 D
Profil	Forestar 668 III
Manufacturer	Alliance
Specification	R1-W, Steel Belted
Recom. Rim	DW20B
Permissible rim	TW20B
Width mm	645
Outer diameter mm	1811
Static radius mm	840
Rolling circumference mm	5410
Payload in kg at kph (1)	5800 / 65
Inflation pressure bar	3,20
Weight kg	298
Tyre content 75% litre	581.25
Stud height mm	53,0
Number of studs	19x2
Certified	ECE 106
Nominal width [mm]	650
Aspect ratio	65
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Alliance 668 Forestar III este o anvelopă radială pentru tractoare forestiere.
- Această anvelopă oferă o tractiune excelentă si o stabilitate excelentă pe soluri umede si noroioase din pădure.
- Crampoanele de umăr late, robuste, precum si o bandă de contact mare asigură o bună stabilitate pe terenuri denivelate.
- Totodată, ea protejează solul pădurii împotriva compactării si a deteriorărilor.
- Carcasa radială rezistentă, cu pereti laterali întăriti si cu centuri din oţel, asigură o lungă perioada de folosintă, chiar si atunci când anvelopa este folosită în cele mai grele conditii.
- În cazul transporturilor pe străzi, această anvelopă se evidentiază printr-un bun confort la rulare.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.