Bohnenkamp
Moving Professionals



Pneu 165 R 13 C, TrailerMove 201
8 PR, 96 / 94 N, TL, M+S
Turon

Product-No.: 10004294

Hints and features:

- Turon TrailerMove 201 este o anvelopă pentru remorci de autoturisme destinat unor cerinte diverse.
- Profilul acesteia oferă o performantă optimă pentru toate utilizările, atât pentru remorci usoare de agrement cât si pentru utilizarea profesională în grădini si amenajarea peisagistică.
- Rezistenta redusă la rulare asigură un consum redus de combustibil.
- Această anvelopă este deosebit de robustă, având o durată lungă de folosintă.
- TrailerMove 201 este utilizabilă la aproape toate mărimile de remorci pentru autoturisme.
- Marca proprie Turon de la Bohnenkamp SE este un nume pentru o fiabilitate ridicată si un excelent raport pret/performanţă.

Technical Information:

Product number	10004294
Tyre Size	165 R 13 C
R / D	Radial
TL / TT	TL
LI / SI	96 / 94 N
PR	8
Profil	TrailerMove 201
Manufacturer	Turon
Specification	M+S
Recom. Rim	4.50J
Width mm	165
Outer diameter mm	594
Payload in kg at kph (1)	710 / 140
Inflation pressure bar	4,50
Weight kg	7,39
Rolling resistance	C
Wet grip	C
Rolling noise DB	71
Rolling noise level	B
Certified	ECE 54, ECE 117
M+S	M+S
Nominal width [mm]	165
Commercial van mark	C
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.