Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 600 / 50 - 22.5, Forestar 644 III 20 PR, 167 A2 / 159 A8, TL, LS-2, Steel Belted Alliance

Product-No.: 10004484

Technical Information:

Product number	10004484
Tyre Size	600 / 50 - 22.5
R / D	Diagonală
TL / TT	TL
LI / SI	167 A2 / 159 A8
PR	20
Profil	Forestar 644 III
Manufacturer	Alliance
Specification	LS-2, Steel Belted
Recom. Rim	AG20.00
Width mm	600
Outer diameter mm	1170
Static radius mm	551
Rolling circumference mm	3602
Payload in kg at kph (1)	5450 / 10
Inflation pressure bar	5,00
Weight kg	154,3
Tyre content 75% litre	205.2
Stud height mm	43,0
Number of studs	15x2
Certified	ECE 106
Nominal width [mm]	600
Aspect ratio	50
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.