Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 380 / 75 R 20, Agro Industrial 580 148 A8 / 148 B, TL, Steel Belted Alliance

Product-No.: 10004493

Technical Information:

Product number	10004493
Tyre Size	380 / 75 R 20
R / D	Radial
TL / TT	TL
LI / SI	148 A8 / 148 B
Profil	Agro Industrial 580
Manufacturer	Alliance
Specification	R4, Steel Belted
Recom. Rim	12
Permissible rim	W12, W11, W13, 13SDC
Width mm	380
Outer diameter mm	1078
Static radius mm	485
Rolling circumference mm	3121
Payload in kg at kph (1)	3150 / 40
Payload in kg at kph (2)	3150 / 50
Inflation pressure bar	4,00
Weight kg	61,4
Tyre content 75% litre	121.73
Stud height mm	36,0
Number of studs	21x2
Certified	ECE 106
Nominal width [mm]	380
Aspect ratio	75
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelope Agro-Industriale / MPT pentru încărcătoare telescopice, încărcătoare frontale pe roti si buldoexcavatoare.
- Carcasa radială puternică asigură capacităti de încărcare ridicate si stabilitate maximă în timpul utilizării.
- Compus de cauciuc optimizat si crampoane centrale unghiulare pentru suprafete dure.
- Rezistentă ridicată la uzură si, prin urmare, o durată lungă de viată.
- Optimă şi adecvată pentru instalatiile de biogaz.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.