Bohnenkamp
Moving Professionals

CEAT SPECIALTY



# Pneu 650 / 50 R 22.5, Floatmax FT
# 163 D, TL, Steel Belted
# CEAT

**Product-No.: 10005040**

**Technical Information:**

| | |
|---|---|
| Product number | 10005040 |
| Tyre Size | 650 / 50 R 22.5 |
| R / D | Radial |
| TL / TT | TL |
| LI / SI | 163 D |
| Profil | Floatmax FT |
| Manufacturer | CEAT |
| Specification | Steel Belted |
| Recom. Rim | AG20.00 |
| Width mm | 645 |
| Outer diameter mm | 1230 |
| Static radius mm | 559 |
| Rolling circumference mm | 3725 |
| Payload in kg at kph (1) | 4875 / 65 |
| Payload in kg at kph (2) | 6630 / 40 |
| Inflation pressure bar | 4,00 |
| Weight kg | 125 |
| Tyre content 75% litre | 308.00 |
| Stud height mm | 23,3 |
| Number of studs | 21x2 |
| Certified | ECE 106 |
| Nominal width [mm] | 650 |
| Aspect ratio | 50 |
| Direction bound | Yes |
| Tread symmetry | simetrice |

**Hints and features:**

- Anvelopa Ceat Floatmax FT este o anvelopă radială pentru remorci agricole.
- Profilul directional al benzii de rulare, cu crampoane robuste, asigură o tractiune foarte bună, aderentă si auto-curătare.
- Blocurile robuste din centrul benzii de rulare si lătimea mare a benzii de rulare permit un comportament bun la rulare în timpul deplasării pe drumuri si o compactare mai redusă a solului în timpul lucrărilor pe câmp.
- Umărul rotunjit al anvelopei previne deteriorarea solului si a plantelor.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.