Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu VF 380 / 105 R 50, Spraymax 179 D, TL, Steel Belted CEAT

Product-No.: 10005362

Hints and features:

- Anvelopa Ceat Spraymax este o anvelopă VF pentru vehicule de pulverizare autopropulsate.
- Datorită tehnologiei VF, anvelopa oferă o capacitate de încărcare cu până la 40% mai mare decât o anvelopă standard sau aceeasi capacitate de încărcare la o presiune de aer cu până la 40% mai mică.
- Crampoanele aranjate sub formă de trepte asigură o bună aderentă si tractiune.
- Umerii rotunjiti ai anvelopei protejează solul si plantele.
- Adâncimea mare a benzii de rulare garantează o durată de viată deosebit de îndelungată.

Technical Information:

Product number	10005362
Tyre Size	VF 380 / 105 R 50
R / D	Radial
TL / TT	TL
LI / SI	179 D
Profil	Spraymax
Manufacturer	CEAT
Specification	Steel Belted
Recom. Rim	W13
Permissible rim	W12
Width mm	383
Outer diameter mm	2050
Static radius mm	944
Rolling circumference mm	6150
Payload in kg at kph (2)	7750 / 40
Inflation pressure bar	4,40
Weight kg	182,01
Tyre content 75% litre	376.00
Stud height mm	38,5
Number of studs	36x2
Certified	ECE 106
Nominal width [mm]	380
Aspect ratio	105
Tyre technology	VF
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.