Bohnenkamp
Moving Professionals



Pneu 385 / 65 R 22.5, Trailer R1
20 PR, 160 K, TL, 3PMSF
TR, Rovelo

Product-No.: 10004967

Hints and features:

Technical Information:

Product number	10004967
Tyre Size	385 / 65 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	160 K
PR	20
Profil	Trailer R1
Manufacturer	Rovelo
Specification	3PMSF
Recom. Rim	11.75
Permissible rim	12.25
Width mm	389
Outer diameter mm	1072
Static radius mm	496
Rolling circumference mm	3248
Inflation pressure bar	9,00
Weight kg	78,17
Rolling resistance	C
Wet grip	C
Rolling noise DB	72
Rolling noise level	B
Stud height mm	15,5
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nominal width [mm]	385
Aspect ratio	65
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.