Bohnenkamp
Moving Professionals



Pneu 285 / 70 R 19.5, Drive R1 18 PR, 150 / 148 K, TL, 3PMSF HA, Rovelo

Product-No.: 10005925

Hints and features:

Technical Information:

Product number	10005925
Tyre Size	285 / 70 R 19.5
R / D	Radial
TL / TT	TL
LI / SI	150 / 148 K
PR	18
Profil	Drive R1
Manufacturer	Rovelo
Specification	3PMSF
Recom. Rim	8.25
Permissible rim	7.50, 9.00
Width mm	283
Outer diameter mm	895
Static radius mm	413
Rolling circumference mm	2730
Inflation pressure bar	9,00
Weight kg	43,81
Rolling resistance	E
Wet grip	B
Rolling noise DB	74
Rolling noise level	B
Stud height mm	16,0
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nominal width [mm]	285
Aspect ratio	70
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.