



## Hints and features:

Pneu 295 / 60 R 22.5, Drive R1  
18 PR, 150 / 147 L, TL, 3PMSF  
HA, Roveló

**Product-No.: 10005928**

## Technical Information:

|                          |                 |
|--------------------------|-----------------|
| Product number           | 10005928        |
| Tyre Size                | 295 / 60 R 22.5 |
| R / D                    | Radial          |
| TL / TT                  | TL              |
| LI / SI                  | 150 / 147 L     |
| PR                       | 18              |
| Profil                   | Drive R1        |
| Manufacturer             | Roveló          |
| Specification            | 3PMSF           |
| Recom. Rim               | 9.00            |
| Permissible rim          | 9.75            |
| Width mm                 | 292             |
| Outer diameter mm        | 926             |
| Static radius mm         | 435             |
| Rolling circumference mm | 2806            |
| Inflation pressure bar   | 9,00            |
| Weight kg                | 56,25           |
| Rolling resistance       | E               |
| Wet grip                 | C               |
| Rolling noise DB         | 74              |
| Rolling noise level      | B               |
| Stud height mm           | 19,0            |
| Certified                | ECE 54, ECE 117 |
| M+S                      | M+S             |
| 3PMSF                    | 3PMSF           |
| Nominal width [mm]       | 295             |
| Aspect ratio             | 60              |
| Tread symmetry           | simetrice       |