Bohnenkamp
Moving Professionals



Pneu 315 / 80 R 22.5, Drive O1
18 PR, 156 / 150 G (154 / 150 J), TL, POR, 3PMSF HA, Rovelo

Product-No.: 10005933

Hints and features:

Technical Information:

Product number	10005933
Tyre Size	315 / 80 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	156 / 150 G (154 / 150 J)
PR	18
Profil	Drive O1
Manufacturer	Rovelo
Specification	3PMSF, POR
Recom. Rim	9.00
Permissible rim	9.75
Width mm	312
Outer diameter mm	1076
Static radius mm	500
Rolling circumference mm	3282
Payload in kg at kph (1)	4000 / 90
Payload in kg at kph (2)	3750 / 100
Inflation pressure bar	8,50
Weight kg	73,2
Stud height mm	23,5
Certified	ECE 54
M+S	M+S
3PMSF	3PMSF
Nominal width [mm]	315
Aspect ratio	80
LI 4	150
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.