Bohnenkamp
Moving Professionals



Hints and features:

Pneu 445 / 65 R 22.5, All Position M2 20 PR, 168 K, TL, 3PMSF VA/HA/TR, Rovelo

Product-No.: 10005934

Technical Information:

Product number	10005934
Tyre Size	445 / 65 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	168 K
PR	20
Profil	All Position M2
Manufacturer	Rovelo
Specification	3PMSF
Recom. Rim	13.00
Permissible rim	14.00
Width mm	444
Outer diameter mm	1150
Static radius mm	529
Rolling circumference mm	3485
Payload in kg at kph (1)	5600 / 110
Inflation pressure bar	8,30
Weight kg	95,04
Rolling resistance	D
Wet grip	C
Rolling noise DB	72
Rolling noise level	B
Stud height mm	16,5
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nominal width [mm]	445
Aspect ratio	65
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.