Bohnenkamp
Moving Professionals

CEAT SPECIALTY

Pneu 440 / 80 R 24, Loadpro Hard Surface 161 A8 / 161 B, TL, Steel Belted CEAT

Product-No.: 10006050

Hints and features:

- Anvelopa Ceat Loadpro Hard Surface este o anvelopă radială MPT pentru manipulatoare telescopice.
- Este extrem de potrivit pentru stivuitoare telescopice, excavatoare si încărcătoare compacte.
- Profilul canelurilor tip bloc non-directionale, cu o înăltime mare al crampoanelor, asigură o tractiune foarte bună si o durată lungă de viată.
- Carcasa din material textil rezistentă cu centuri din otel (Steel Belted) si amestecul de cauciuc de înaltă calitate al benzii de rulare si a peretilor laterali fac ca anvelopa să fie deosebit de stabilă si să protejeze împotriva deteriorărilor.
- Talonul său ranforsat asigură stabilitate si un montaj simplu.

Technical Information:

Product number	10006050
Tyre Size	440 / 80 R 24
R / D	Radial
TL / TT	TL
LI / SI	161 A8 / 161 B
Profil	Loadpro Hard Surface
Manufacturer	CEAT
Specification	Steel Belted
Recom. Rim	W14
Permissible rim	DW13, W15L
Width mm	465
Outer diameter mm	1312
Static radius mm	584
Rolling circumference mm	3916
Payload in kg at kph (1)	4625 / 40
Payload in kg at kph (2)	4625 / 50
Inflation pressure bar	4,00
Weight kg	118
Tyre content 75% litre	247.00
Stud height mm	33,5
Number of studs	25x2
Certified	ECE 106
Nominal width [mm]	440
Aspect ratio	80
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.