Bohnenkamp
Moving Professionals

CEAT SPECIALTY

Pneu IF 1250 / 50 R 32 CFO, Yieldmax IFLEX 201 D, TL, Steel Belted
CEAT

Product-No.: 10006481

Technical Information:

Product number	10006481
Tyre Size	IF 1250 / 50 R 32 CFO
R / D	Radial
TL / TT	TL
LI / SI	201 D
Profil	Yieldmax IFLEX
Manufacturer	CEAT
Specification	R1-W, Steel Belted
Recom. Rim	DH44HB
Width mm	1247
Outer diameter mm	2063
Static radius mm	901
Rolling circumference mm	6157
Payload in kg at kph (2)	14500 / 40
Inflation pressure bar	3,20
Weight kg	635
Stud height mm	57,5
Number of studs	20x2
Certified	ECE 106
Cyclic field use	CFO
Nominal width [mm]	1250
Aspect ratio	50
Tyre technology	IF
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopa Ceat Yieldmax IFLEX este o anvelopă radială IF pentru vehicule de recoltare.
- Această anvelopă extra-lată oferă o mare suprafată de contact pentru o foarte bună distribuire a presiunii si pentru conservarea solului.
- Profilul cu crampoane care se suprapun, din mijlocul suprafetei de rulare, asigură o foarte bună tracţiune si totodată confort de rulare, precum si o uzură lentă.
- Constructia IF permite capacităti de încărcare cu 20% mai mari la aceeasi presiune a aerului sau aceleasi capacităti de încărcare la o presiune a aerului redusă cu până la 20% în comparatie cu anvelopa standard.
- Umerii rotunjiti ai anvelopei protejează solul si plantele în cazul utilizării pe câmp.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.