Bohnenkamp
Moving Professionals

KENDA



Pneu 250 - 15, K610 Kinetics
20 PR, TT
(250/70-15), cam.+flap, TR 77 A, Kenda

Product-No.: 19271096

Hints and features:

- Anvelope pneumatice pentru stivuitoare si stivuitoare de containere
- Anvelopă rezistentă si fiabilă cu o durată lungă de viată.
- Tractiune excelentă si suprafată de contact mare
- Ranforsarea suplimentară a carcasei asigură o suprafată de contact uniformă.

Technical Information:

Product number	19271096
Tyre Size	250 - 15
R / D	Diagonală
TL / TT	TT
LI / SI	20 PR
PR	20
Profil	K610 Kinetics
Manufacturer	Kenda
Specification	Tub + bandă talon
Recom. Rim	7.5
Width mm	240
Outer diameter mm	742
Payload in kg at kph (1)	4844 / 25
Payload in kg at kph (2)	3875 / 25
Inflation pressure bar	10,00
Weight kg	38,08
Stud height mm	18,5
Certified	nu este necesar
Nominal width [mm]	250
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.