Bohnenkamp
Moving Professionals

KENDA



Pneu 8.15 - 15, K610 Kinetics
14 PR, TT
(28x9-15), cam.+flap, TR 75 A, Kenda

Product-No.: 19271094

Hints and features:

- Anvelope pneumatice pentru stivuitoare si stivuitoare de containere
- Anvelopă rezistentă si fiabilă cu o durată lungă de viată.
- Tractiune excelentă si suprafată de contact mare
- Ranforsarea suplimentară a carcasei asigură o suprafată de contact uniformă.

Technical Information:

Product number	19271094
Tyre Size	8.15 - 15
R / D	Diagonală
TL / TT	TT
LI / SI	14 PR
PR	14
Profil	K610 Kinetics
Manufacturer	Kenda
Specification	Tub + bandă talon
Recom. Rim	7.0
Width mm	230
Outer diameter mm	710
Payload in kg at kph (1)	3750 / 25
Payload in kg at kph (2)	3000 / 25
Inflation pressure bar	10,00
Weight kg	29,09
Stud height mm	17,5
Certified	nu este necesar
Nominal width [inch]	8.15
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.