Bohnenkamp
Moving Professionals



Pneu 8.25 - 20, TerraClassic SKL800
14 PR, 133 B, TT
cam.+flap, TR 442, Turon

Product-No.: 10003463

Hints and features:

- Turon TerraClassic SKL 800 este adecvată pentru utilaje de constructii precum excavatoare, încărcătoare pe roti si încărcătoare telescopice.
- Combinatia sa specială de cauciucuri asigură o durabilitate foarte bună, chiar si atunci când este utilizată pe terenuri dificile, pietroase.
- Contructia sa diagonală, cu pereti laterali întăriti, protejează în mod sigur anvelopele împotriva detriorărilor.

Technical Information:

Product number	10003463
Tyre Size	8.25 - 20
R / D	Diagonală
TL / TT	TT
LI / SI	133 B
PR	14
Profil	TerraClassic SKL800
Manufacturer	Turon
Specification	Tub + bandă talon
Recom. Rim	6.50
Permissible rim	7.0
Width mm	245
Outer diameter mm	992
Static radius mm	448
Rolling circumference mm	2887
Payload in kg at kph (1)	2060 / 50
Inflation pressure bar	6,75
Weight kg	34
Stud height mm	19,0
Certified	nu este necesar
Nominal width [inch]	8.25
Direction bound	Yes
Tread symmetry	simetrice

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.