Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu VF 580 / 85 R 42, Torquemax 183 D, TL, Steel Belted CEAT

Product-No.: 10007883

Technical Information:

Product number	10007883
Tyre Size	VF 580 / 85 R 42
R / D	Radial
TL / TT	TL
LI / SI	183 D
Profil	Torquemax
Manufacturer	CEAT
Specification	R1-W, Steel Belted
Recom. Rim	DW18B
Permissible rim	DW20B, DW21B
Width mm	585
Outer diameter mm	2050
Static radius mm	898
Rolling circumference mm	6054
Inflation pressure bar	2,80
Weight kg	86
Tyre content 75% litre	498.75
Stud height mm	55,3
Number of studs	23x2
Certified	ECE 106
Nominal width [mm]	580
Aspect ratio	85
Tyre technology	VF
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopa Ceat Torquemax este o anvelopă pentru tractoare de înaltă performantă.
- Designul său asigură o compactare mai redusă a solului, o tractiune ridicată si o bună manevrabilitate atât pe câmp, cât si la transportul pe sosea.
- Crampoanele anvelopei sunt usor înclinate în centrul benzii de rulare pentru a asigura caracteristici bune de rulare pe sosea.
- Unghiul mai plat al crampoanelor de pe umărul anvelopei asigură o tractiune excelentă în timpul lucrărilor pe câmp.
- Umerii rotunjiti ai anvelopei protejează solul si plantele.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.