Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



# Pneu 6.5 / 80 - 15, 324
# 6 PR, 98 A6 / 94 A8, TT
# Alliance

**Product-No.: 15211600**

**Hints and features:**

- Anvelope AS cu straturi încrucisate pentru utilizare pe tractoare sau ca anvelope pentru utilaje.
- Crampoane dispuse la un unghi de 45° pentru tractiune ridicată si auto-curătare bună chiar si în cele mai dificile conditii.
- Carcasa puternică din nailon asigură siguranta operațională si o transmisie bună a tractiunii.

**Technical Information:**

| | |
|---|---|
| Product number | 15211600 |
| Tyre Size | 6.5 / 80 - 15 |
| R / D | Diagonală |
| TL / TT | TT |
| LI / SI | 98 A6 / 94 A8 |
| PR | 6 |
| Profil | 324 |
| Manufacturer | Alliance |
| Recom. Rim | 5.00F |
| Width mm | 166 |
| Outer diameter mm | 676 |
| Static radius mm | 295 |
| Rolling circumference mm | 1942 |
| Payload in kg at kph (1) | 750 / 30 |
| Payload in kg at kph (2) | 670 / 40 |
| Inflation pressure bar | 3,60 |
| Weight kg | 10,89 |
| Tyre content 75% litre | 210.75 |
| Stud height mm | 16,0 |
| Certified | ECE 106 |
| Nominal width [inch] | 6.5 |
| Aspect ratio | 80 |
| Direction bound | Yes |
| Tread symmetry | simetrice |

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.