Bohnenkamp
Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD



Pneu 405 / 70 R 20, 570
155 A2 / 143 B, TL, Steel Belted
Alliance

Product-No.: 15225014

Technical Information:

Product number	15225014
Tyre Size	405 / 70 R 20
R / D	Radial
TL / TT	TL
LI / SI	155 A2 / 143 B
Profil	570
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	13
Width mm	421
Outer diameter mm	1080
Static radius mm	495
Rolling circumference mm	3291
Payload in kg at kph (1)	3875 / 10
Payload in kg at kph (2)	2725 / 50
Inflation pressure bar	3,75
Weight kg	64,8
Tyre content 75% litre	108.56
Stud height mm	26,0
Number of studs	20x2
Certified	ECE 106
Nominal width [mm]	405
Aspect ratio	70
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopă radială MPT pentru o gamă largă de aplicatii.
- Potrivit în special pentru utilizarea pe masinile de recoltat.
- Bandă de rulare în formă de AS pentru o tractiune bună atunci când este utilizată pe terenuri arabile.
- Capacitate mari de încărcare chiar si la presiuni scăzute ale aerului.
- Carcasă textilă radială cu centură de armare din otel.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.