Bohnenkamp
Moving Professionals

CEAT SPECIALTY



Pneu VF 750 / 70 R 44, Torquemax 186 D, TL, Steel Belted CEAT

Product-No.: 10006657

Technical Information:

Product number	10006657
Tyre Size	VF 750 / 70 R 44
R / D	Radial
TL / TT	TL
LI / SI	186 D
Profil	Torquemax
Manufacturer	CEAT
Specification	R1-W, Steel Belted
Recom. Rim	DW25B
Permissible rim	DW24B
Width mm	760
Outer diameter mm	2180
Static radius mm	950
Rolling circumference mm	6460
Inflation pressure bar	2,00
Weight kg	405
Stud height mm	65,0
Number of studs	23x2
Certified	ECE 106
Nominal width [mm]	750
Aspect ratio	70
Tyre technology	VF
Direction bound	Yes
Tread symmetry	simetrice

Hints and features:

- Anvelopa Ceat Torquemax este o anvelopă pentru tractoare de înaltă performantă.
- Designul său asigură o compactare mai redusă a solului, o tractiune ridicată si o bună manevrabilitate atât pe câmp, cât si la transportul pe sosea.
- Crampoanele anvelopei sunt usor înclinate în centrul benzii de rulare pentru a asigura caracteristici bune de rulare pe sosea.
- Unghiul mai plat al crampoanelor de pe umărul anvelopei asigură o tractiune excelentă în timpul lucrărilor pe câmp.
- Umerii rotunjiti ai anvelopei protejează solul si plantele.

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp SRL does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.